

DS-600VS MODEL STRAPPING MACHINE

SAFE, EASY TO OPERATE, STAINLESS FRAME.



FEATURES:

Safety

24VDC electric eliminates possibility of machine electrical shocks.

Anti-Rust Side Seal Head

The DS-600VS strapping head is installed in the vertical position to minimise rust and prevent any strap contamination.

Pack Size

A large variety of package sizes are suitable for strapping in this machine. No tools are needed to adjust any of the 20 section height adjustments between 450 and 850 mm.


Simple Maintenance

It is very easy to replace and maintain the changeable PC circuit board. Maintenance on the side seal head can also be done safely and easily.

Extra Equipments

The machine can be installed the following extra equipments according to the customer's requirement.

- 1) To use stainless roller for feed or reset strap (inner mechanism).
- 2) To enlarge the area (length or width) of packing table.
- 3) To change casters into stainless casters.
- 4) To install the small lamp inside of machine for remaining the inner of mechanism more dry.



Specifications:

Strapping Speed	1.5sec/strap
Minimum Package Size	60mm
Maximum Package Size	Any Size
Maximum Strength	65 kgs
Strap Width	6mm-15mm
Power	AC 110/220V (50/60Hz)
Driving Motors	220V/110V 200W
Dimension	675mm (W) x 1045mm (D) x 1720mm (H)
Net Weight	130 kgs
Gross Weight	192kgs