

SEMI-AUTOMATIC HORIZONTAL BAND SAWS





**MOD.: SABS-450
SABS-760**

STANDARD FEATURES

1. CARBIDE AND ROLLER BLADE GUIDES
2. AUTOMATIC HEAD ELEVATION CONTROL
3. POWER-DRIVEN BLADE CLEANING BRUSH
4. HYDRAULIC QUICK-SETTING VISE
5. COOLANT CLEANING FLUSH HOSE
6. QUICK ADJUSTING CARBIDE SAW GUIDE
7. PRESSURE COMPENSATION FEED-RATE CONTROL
8. MOTORIZED TURN TABLE MITRE CUTTING DEVICE

STANDARD ACCESSORIES

1. TOOLS WITH TOOL BOX.....1 PC
2. BLADE CLEANING WIRE BRUSH ..2 PCS
3. BAND SAWBLADE.....1 PC
4. INSTRUCTION MANUAL.....1 COPY



SEMI-AUTOMATIC HORIZONTAL BAND SAWS

SPECIFICATION	SASS-450	SASS-760
CUTTING CAPACITY	●SOLID 320 MM DIA.	●SOLID 460 MM DIA.
AT 90°	■SOLID 320 × 320 SQR.	■SOLID 460 MM SQR
H BEAMS/PIPES	⊙320 MM O.D. □/∕H 510 SQR. 510 × 320	⊙460 MM O.D. □/∕H 760 × 400 MM
MITRE CUTTING	●SOLID 300 MM DIA.	●SOLID 420 MM DIA.
AT 60°	●SOLID 300 MM SQR.	●SOLID 420 MM SQR.
H BEAMS/PIPES	⊙320 MM DIA. □/∕H 357 × 320 MM	⊙460 MM O.D. □/∕H 3590 × 400 MM
MITRE CUTTING	●SOLID 250 MM DIA.	●SOLID 330 MM DIA.
AT 45°	●SOLID 250 MM SQR.	■SOLID 330 MM SQR.
H BEAMS/PIPES	⊙320 MM DIA. □/∕H 213 × 320 MM	⊙460 MM O.D. □/∕H 500 × 400 MM
MITRE CUTTING	●SOLID 83 MM DIA.	●SOLID 220 MM DIA.
AT 30°	●SOLID 83 MM SQR.	■SOLID 220 MM SQR.
H BEAMS/PIPES	⊙83 MM DIA. □/∕H 83×320 MM	⊙220 MM O.D. □/∕H 220×400 MM
BLADE SIZE	34 × 1.1 × 4115 MM 1.25 × .042 × 162 IN	38 × 1.3 × 5300 MM 1½ × .051 × 209 IN
BLADE SPEED M/MIN	25 - 80 M/MIN (50/60HZ)	15 - 150 M/MIN
MOTOR OUTPUT	BLADE 5 HP (3.7 KW) HYD. 1 HP (0.75 KW) CLNT 1/8 HP (0.1 KW)	BLADE 7.5 HP (5.62 KW) HYD. 2 HP (1.5 KW) CLNT 1/4 HP (.19 KW)
SHIPPING VOLUMN	2220 × 1650 × 1450 MM	2805 × 2300 × 2100 MM
WEIGHT NET/GROSS	1770 / 1970 KGS	2600 / 2900 KGS

MODEL/SPEC	A	B	C	D	E	F
SABS-450	1810	1132	635	1750	1930	2100
	71.3"	44.6"	25.0"	68.9"	76.0"	82.7"
SABS-760	2400	1350	630	2200	2040	2600
	94.5"	53.1"	24.8"	86.6"	80.3"	102.4"

- SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE FOR IMPROVEMENT AND MODIFICATION.



FULLPOWER®

富堡實業有限公司

FULPOW INDUSTRIAL CORP.

7F-2, NO. 400, SEC. 1, CHANG PING ROAD, TAICHUNG, TAIWAN
TEL: 886-4-2243 9235 (REP.) FAX: 886-4-2244 3829

E-MAIL: fulpow@ms7.hinet.net